


STANDARD
CABLE TIE



ARTICLE	NAME	L, MM	W, MM	MAX. Ø, MM	LOOP STRENGTH LIMIT, KG	QUANTITY IN PACKAGING, PCS	PACKAGING IN A BOX, PACK	QUANTITY IN BOX, PCS	BOX WEIGHT, KG	BOX TYPE
CT3X100	2,5x100	100	2,5	22	8	100	280	28000	9,3	A
CT3X150	2,5x150	150	2,5	35	8	100	210	21000	10,7	A
CT3X200	2,5x200	200	2,5	50	8	100	160	16000	12,2	A
CT3X250	2,5x250	250	2,5	65	8	100	140	14000	12,4	A
CT4X150	3,6x150	150	3,6	35	18	100	120	12000	11,0	A
CT4X200	3,6x200	200	3,6	50	18	100	100	10000	12,1	A
CT4X250	3,6x250	250	3,6	65	18	100	80	8000	11,2	A
CT4X300	3,6x300	300	3,6	80	18	100	70	7000	12,1	A
CT4X370	3,6x370	370	3,6	100	18	100	60	6000	12,5	A
CT5X200	4,6x200	200	4,6	50	22	100	70	7000	13,6	A
CT5X250	4,6x250	250	4,6	65	22	100	65	6500	11,2	A
CT5X300	4,6x300	300	4,6	80	22	100	50	5000	12,1	A
CT5X350	4,6x350	350	4,6	90	22	100	45	4500	17,4	A
CT5X400	4,6x400	400	4,5	105	22	100	50	5000	13,6	B
CT5X450	4,6x450	450	4,05	120	22	100	50	5000	15	B
CT5X500	4,6x500	500	4,6	150	22	100	45	4500	16,8	B
CT8X300	7,6x300	300	7,6	80	55	100	30	3000	12,5	A
CT8X400	7,6x400	400	7,6	105	55	100	30	3000	15,7	B
CT8X500	7,6x500	500	7,6	150	55	100	25	2500	16,3	B
CT9X650	8,8x650	650	8,8	190	100	100	10	1000	10,2	B
CT9X760	8,8x760	760	8,8	225	100	100	10	1000	13,6	B



INSTALLATION TEMPERATURE -10°C ÷ 60°C
MOISTURE ABSORPTION 2,7% (23°C - 50% R.H.)
FIRE RESISTANCE OF MATERIAL UL 94-V2 Halogen-free
RESISTANCE TO aromatic solvents, oils, greases and their derivatives.
RESISTANT ultraviolet exposure
LIMITED RESISTANCE acids
NON-RESISTANT phenols and chlorinated solvents
WORKING TEMPERATURE -40°C ÷ 85°C
MATERIAL polyamide 6.6 natural (+ 1% carbon black for the black version)

COLOR PALLETTE



Standard colors: natural, black. The colors indicated in the palette are available for production. The minimum quantity for production in non-standard palette can be negotiated individually. The products correspond with the EN 62275:2015; EN50581:2012 standards and the requirements of : Voltage Directive 2014/35/EU, RoHS Directive 2011/65/EU.

